

# **MATTE LAMINATION FILM(SP111-0970)**

## **SPECIFICATION**

<b>Face</b>	<b>Material</b>	<b>BOPP film</b>	
	<b>Basis Weight</b>	<b>15±3g/m<sup>2</sup></b>	ISO536
	<b>Thickness</b>	<b>20±3μ</b>	ISO534
	<b>Tear strength</b>	<b>≥20N/2.5CM</b>	ISO1924/1
<b>Adhesive</b>	<b>Glue Type</b>	<b>Acrylic solution based</b>	
	<b>Coating Weight</b>	<b>11-12g/m<sup>2</sup></b>	ISO536
	<b>Thickness</b>	<b>10-11μ</b>	ISO534
<b>Physical Data</b>	<b>Peel adhesion</b>	<b>≥2.0 N/2.5cm</b>	(FTM1 (180° s. steel))
	<b>Initial tack</b>	<b>≥2.0 N/6.25 cm<sup>2</sup></b>	FTM9 glass)
	<b>Holding Power</b>	<b>≥12h</b>	
	<b>Service Temp</b>	<b>-10 ~ 60 °C</b>	
	<b>Min. application temp</b>	<b>10 °C</b>	
	<b>Max. Application temp</b>	<b>40 °C</b>	
<b>Application</b>	Laminating of the protection for covering the printed labels; Used in the paper, PET, PP synthetic paper such as labels fields.		
<b>Shelf Life &amp; Storage</b>	In Dry and cool place and away direct from sunlight. From the date of manufacture 1 year stored at 23±2°C and RH 50±5% in original packaging.		
<b>Warranty</b>	The information given is based on our knowledge and experience; and is given in good faith. It does not represent a guarantee or legal warranty for specific properties of for suitability for a specific use. The products are used in conditions beyond our control; we cannot assume any liability for damage caused through their use. It is highly recommended to take certain test prior to use of this product(s), to ensure it meets the requirement and/or suitability for use under end-use conditions. We reserve the right for the technical innovation of the product(s).		
<b>Product Info</b>	Product Width	1090 mm (1070 mm usable)	
	Product length	200m, 400m	