



Technical Data

DS3# DOUBLE SIDED TISSUE TAPE

Description - DS3# has been developed to provide high adhesion and superior long term aging characteristics. A **14 g/m²** light weight tissue stock coated on both sides with a Transparent acrylic adhesive, easy release liner. **Meets UL Listed # MH13008 – DS3# and RoHS regulations.**

Application - Developed for nameplate mounting or where excellent solvent resistance and extra high shear strength properties are required such as fixing golf club grips etc.

Technical Details:

<u>Properties</u>	<u>Unit</u>	<u>Average Test Values</u>
Total Weight	g/sqm	125
Tensile Strength	Kg/25mm	↑ 1.5
Adhesion To Steel	Kg/25mm	↑ 0.9
Holding Power (25mm X 25mm X 2kg)	Min	↑ 1020

Performance Data:

The performance of 180° peeling adhesion at varieties of foam surfaces at room temperature.

	kg/25mm	
	Close side	Open side
EVA foam	0.55	0.79
PE foam	0.25	0.31

Shelf Life : 12 months when storage in original carton at 23°C and 65% relative humidity..

Test Method : In accordance with ASTM D-1000.

Availability : Standard 22M per roll. 77i.d. core. Log roll maximum width 1220mm

Color : Semi-transparent.

Shelf Life : 12 months when storage in original carton at 23°C and 65% relative humidity.

Test Method : In accordance with ASTM D-1000.

Availability : Standard length 50M, 1000M, 77(3") i.d. core. Log roll max. 1220mm.

Important Notice to Purchaser

All statement, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, users shall determine the suitability of the product for their intended use, and users assume all risk and liability whatsoever in connection therewith.

No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacture.

FOUR PILLARS ENTERPRISE CO., LTD.

No. 12, Lane 61, Sec. 1, Kuang Fu Rd, San Chung City, 241 Taipei, Taiwan, R.O.C

TEL:886-2-2999-1133 FAX:886-2-2999-1136 or 2999-2284 <http://www.fourpillars.com.tw>

