


## OPP Application Tape

### TR43

#### Application :

TR43 is the mid tack transfer tape with 0.040mm thick transparent OPP film backing and acrylic base adhesive. It is designed for machine usage, which can reduce the necessary human resource when transfer any label stock on items, and save more time.

#### Structure :



#### Specialty :

- OPP backing has great stiffness, which is suitable for peel and stick.
- After process finished, there will be no residue on the surface after removed.
- Acrylic base adhesive has great adhesion on high surface energy material, such as steel, PET...etc.

#### Technical Data :

Properties	Unit	Average Test Value
Total Thickness	mm	0.060 ±10%
180° Peel Adhesive	g/25mm	150±50
Unwinding Force	min/25mm	1000↑

Test Method: ASTM D-1000

**Storage Condition :** 23°C, 65 % R.H

#### IMPORTANT NOTICE TO PURCHASER

All statements technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, users shall determine the suitability of the product for their intended use, and users assume all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacturer.

[www.avataackco.com](http://www.avataackco.com)

## Remark :

1. Before using this product, in order to make sure the quality of the adhesion, please clean all the dust, water, oil, or any other dirt on the surface.
2. Above figures are for reference and cannot be treated as warranties. Customers are advised to test the material to determine the suitability against intended applications.
3. One Year Storage life; Suggested preservation temperature 23°C , 65% RH .
4. Best operation temperature is from 20~60°C . The adhesion will decrease if operate under 10°C .

- 
- Ⓢ The above information is for reference only and should not be employed as inspection standard.

## IMPORTANT NOTICE TO PURCHASER

All statements technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, users shall determine the suitability of the product for their intended use, and users assume all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacturer.